

What is claimed is:

1. A printing-fluid container, comprising:  
a reservoir configured to hold printing fluid, the reservoir defining a well in a gravitationally low portion of the reservoir; and  
5 a fluid interface configured to releasably receive a fluid connector to draw printing fluid from the well.
2. The printing-fluid container of claim 1, wherein the fluid interface includes a septum mounted on the reservoir to receive a horizontally-inserted  
10 fluid connector.
3. The printing-fluid container of claim 2, wherein the fluid interface further includes a spring member and a plug member, and wherein the spring member yieldably biases the plug member against the septum to create a fluid  
15 tight seal.
4. The printing-fluid container of claim 1, wherein the reservoir includes a bottom surface configured to gravitationally direct printing fluid toward the well.  
20
5. The printing-fluid container of claim 4, wherein the bottom surface includes a trough portion that protrudes downwardly from a remaining portion of the bottom surface, and wherein the well is at least partially defined by the trough portion.  
25
6. The printing-fluid container of claim 1, further comprising an air interface located above the fluid interface.
7. The printing-fluid container of claim 6, wherein the fluid interface  
30 and the air interface are vertically aligned on a substantially planar face of the printing-fluid container.

8. The printing-fluid container of claim 1, wherein a cross-sectional area of the reservoir in the well is less than a cross-sectional area of the reservoir above the well.

5 9. The printing-fluid container of claim 8, wherein the cross-sectional area of the reservoir in the well is at most half the cross-sectional area of the reservoir above the well.

10 10. The printing-fluid container of claim 1, wherein the fluid interface and the well are cooperatively configured to deliver printing fluid from the reservoir until such reservoir is at least 90% drained.

15 11. The printing-fluid container of claim 1, wherein the fluid interface and the well are cooperatively configured to leave a volume of stranded printing fluid which is no more than approximately 5% of a volume of the reservoir.

20 12. The printing-fluid container of claim 1, wherein the fluid interface and the well are cooperatively configured to provide for delivery of printing fluid from the reservoir until no more than approximately 2 cubic centimeters of printing fluid remains in the reservoir.

25 13. The printing-fluid container of claim 1, wherein the fluid interface and the well are cooperatively configured to provide for delivery of printing fluid from the reservoir until no more than approximately 1 cubic centimeter of printing fluid remains in the reservoir.

14. The printing-fluid container of claim 1, further comprising a free volume of ink held within the reservoir.

30 15. The printing-fluid container of claim 1, further comprising a free volume of preconditioner held within the reservoir.

16. The printing-fluid container of claim 1, further comprising a free volume of fixer held within the reservoir.

17. A printing-fluid container configured for lateral installation in a printing system, the printing-fluid container comprising:

a reservoir configured to hold a printing fluid, the reservoir defining a protruding well into which printing fluid is gravitationally pulled; and

a fluid interface configured to access the reservoir from laterally adjacent the well when the printing-fluid container is installed.

18. The printing-fluid container of claim 17, wherein the fluid interface includes a septum configured to receive a horizontally inserted fluid connector.

19. The printing-fluid container of claim 18, wherein the fluid interface further includes a spring member and a plug member, and wherein the spring member biases the plug member against the septum to create a fluid tight seal when the printing-fluid container is installed.

20. The printing-fluid container of claim 17, further comprising an air-interface located above the fluid interface.

21. The printing-fluid container of claim 17, wherein a cross-sectional area of the reservoir in the well is less than a cross-sectional area of the reservoir immediately above the well.

22. The printing-fluid container of claim 17, further comprising a free volume of ink held within the reservoir.

23. The printing-fluid container of claim 17, further comprising a free volume of preconditioner held within the reservoir.

24. The printing-fluid container of claim 17, further comprising a free volume of fixer held within the reservoir.

25. A printing-fluid container, comprising:

5 a reservoir defining an inner cavity configured to hold a free volume of printing fluid, wherein the free volume of printing fluid has a fluid level that lowers as the printing-fluid container is emptied; and

a fluid interface positioned on an upright face of the reservoir to accommodate draining of the free volume of ink until not more than 10% of the  
10 inner cavity contains the free volume of ink.

26. The printing-fluid container of claim 25, wherein the fluid interface is positioned to accommodate draining of the free volume of ink until the free volume of ink occupies not more than 5% of the inner cavity.

15

27. The printing-fluid container of claim 25, wherein the fluid interface is positioned to accommodate draining of the free volume of ink until the free volume of ink occupies not more than 2% of the inner cavity.

20 28. A printing-fluid container for installation in a printing system, the printing-fluid container comprising:

means for holding a volume of printing fluid, wherein the means for holding defines a bottom well of reduced cross-sectional area;

means for gravitationally directing printing fluid into the well; and

25 means for laterally receiving a fluid connector to draw printing fluid from the well.

29. The printing-fluid container of claim 28, wherein the bottom well is configured to contain a volume of printing fluid which is less than 10% of a  
30 volume of the means for holding.

30. A printing-fluid container, comprising:  
a reservoir configured to hold a free volume of ink, the reservoir including  
an upright face with a downwardly-extending protrusion; and  
a fluid interface positioned on the downwardly-extending protrusion and  
5 configured to access the free volume of ink.

31. The printing-fluid container of claim 30, wherein the fluid interface  
includes a septum configured to receive a horizontally inserted fluid connector.

10 32. The printing-fluid container of claim 31, wherein the fluid interface  
further includes a spring member and a plug member, and wherein the spring  
member yeildably biases the plug member against the septum to create a fluid  
tight seal.

15 33. The printing-fluid container of claim 30, further comprising an air  
interface located above the fluid interface.

34. A printing-fluid container configured for lateral insertion in a  
container bay of a printing system, the printing-fluid container comprising:  
20 a leading surface;  
a top surface;  
a bottom surface;  
an air interface positioned on the leading surface proximate the top  
surface; and  
25 a printing-fluid interface positioned on the leading surface proximate the  
bottom surface.

35. The printing-fluid container of claim 34, wherein the printing-fluid  
interface is positioned within 10 millimeters of the bottom surface.

36. The printing-fluid container of claim 35, wherein the air interface is positioned within 10 millimeters of the top surface.

37. The printing-fluid container of claim 34, wherein the printing-fluid interface is positioned within 5 millimeters of the bottom surface.

38. The printing-fluid container of claim 37, wherein the air interface is positioned within 5 millimeters of the top surface.

39. The printing-fluid container of claim 34, wherein the leading surface includes a downwardly-extending protrusion and the bottom surface defines a downwardly-extending well substantially aligned with the downwardly-extending protrusion, and wherein the printing-fluid interface is positioned on the downwardly-extending protrusion to access the downwardly-extending well.

40. The printing-fluid interface of claim 39, wherein the downwardly-extending protrusion is horizontally centered on the leading surface.

41. The printing-fluid container of claim 39, wherein the printing-fluid interface and the air interface are vertically aligned.

42. The printing-fluid container of claim 41, wherein the printing fluid interface and the air interface are horizontally centered on the leading surface.

43. The printing-fluid container of claim 39, wherein the printing-fluid interface is configured to releasably laterally receive a fluid connector into a position to draw printing fluid from the downwardly-extending well.

44. The printing-fluid container of claim 34, wherein the printing-fluid interface is horizontally centered in the container bay upon lateral insertion of the container in the container bay.

45. The printing-fluid container of claim 34, wherein the printing-fluid interface and the air interface are vertically aligned.

46. A printing-fluid container configured for lateral insertion in a container bay, the printing-fluid container comprising:

a reservoir defining an inner cavity configured to hold a volume of printing fluid, the reservoir having an upright leading surface with a downwardly-extending protrusion and a bottom surface defining a downwardly-extending well substantially aligned with the downwardly-extending protrusion; and

a fluid interface positioned on the downwardly-extending protrusion and configured to releasably receive a fluid connector into a position to draw printing fluid from the downwardly-extending well, wherein the fluid interface is horizontally centered in the container bay upon insertion of the printing-fluid container in the container bay.

15

47. The printing-fluid interface of claim 46, wherein the downwardly-extending protrusion is horizontally centered on the leading surface.

48. The printing-fluid container of claim 47, wherein the fluid interface is positioned within 10 millimeters of the bottom surface.

20

49. The printing-fluid container of claim 46, wherein the fluid interface includes a horizontal passage through which the fluid connector may pass.

50. The printing-fluid container of claim 46, wherein the bottom surface includes a slanting portion configured to gravitationally direct printing fluid to the downwardly-extending well.

25

51. A method of delivering a printing fluid, comprising:
- holding a free volume of printing fluid in a reservoir that includes a fluid interface and a well positioned at a bottom of the reservoir when the reservoir is in a seated orientation; and
  - 5 drawing printing fluid via the fluid interface from the well such that fluid may be drawn until the reservoir is more than 90% empty.